




PRODUCT DATA DRAWING

REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
A	DCN 41763	10/15	MAL



MATERIAL:

BODIES, CONTACTS, & COUPLING NUT:	BRASS PER ASTM B16, ALLOY UNS No. C36000
LOCK RING:	PHOSPHOR BRONZE PER ASTM B159, ALLOY 51000
OUTER CONTACT:	BERYLLIUM COPPER PER ASTM B194, ALLOY No. UNS C17200
INSULATORS:	PTFE PER ASTM D1710, TYPE I, GRADE 1, CLASS B
GASKET:	SILICONE RUBBER PER A-A-59588, CLASS 2B, GRADE 50/60

FINISH:

BODIES, OUTER CONTACT, COUPLING NUT, & CRIMP SLEEVE:	SILVER PER ASTM B700, TYPE 1, GRADE D, CLASS S
CONTACTS:	GOLD PER ASTM B488, TYPE II, CODE C, CLASS 1.27, OVER NICKEL PER AMS-QQ-N-290, CLASS 1, .00005" MIN.

PERFORMANCE:

IMPEDANCE:	50 OHMS
FREQ. RANGE:	DC TO 11.0 GHz

MATERIAL:	SEE NOTES	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ±1/64 ANGULAR: X° ±1°0'
-----------	-----------	---