

NOTES:

1. MATERIALS AND FINISH (IN MICRO-INCHES)

BODY = ZINC DIECAST (PER ASTM B86), MATTE TIN PL.
INSULATOR = PTFE PER ASTM D1710, COLOR: NATURAL
HOUSING = PPE+PS, COLOR:PER TABLE
FERRULE = COPPER (PER ASTM B75),NICKEL PL.
O-RING = SILICONE RUBBER, COLOR: RED
SHRINK TUBING = POLYOLEFIN, ADHESIVE LINED, COLOR: BLACK

CONTACT SUPPLIED SEPARATELY AS P/N: FKCP08402 (5,000 PCS. REEL)
CABLE DEFINITIONS PER AMPHENOL REPORT DE825

2. ELECTRICAL:

A. IMPEDANCE: 50 OHM, NOMINAL
B. FREQUENCY RANGE: DC-3.0 GHz
C. VSWR(RETURN LOSS): 1.200 (-20.8dB) MAX.(DC-200 MHz)
(MATED PAIR) 1.400 (-15.6dB) MAX.(200 MHz-2.0 GHz)
1.500 (-13.9dB) MAX.(2.0-3.0 GHz)
D. D.W.V.: 800 VRMS, MIN.

3. MECHANICAL:

A. DURABILITY: 100 CYCLES MIN.
B. TEMPERATURE RANGE: -40° C TO 85° C
C. USCAR-17 COMPLIANT
D. INTERFACE PER DIN 72594-1
E. ENVIRONMENTAL SEAL (WHEN MATED): IP67

4. PACKAGING:

A. QUANTITY: TRAY PACK
B. MARKING: TRAY TO BE MARKED
"AMPHENOL RF, 3FAIENXSJ-COIES, AND DATE CODE"

5. CABLE ASSEMBLY INSTRUCTIONS PER 349-50910

THIRD ANGLE PROJ.

CONFIGURATION CONTROL:
NO CHANGES PERMITTED TO DRAWING WITHOUT
PPAP QUALIFIED CUSTOMER APPROVAL

14.4

8.2

2.5

RECOMMENDED
CABLE STRIPPING DIMENSIONS

REV

DESCRIPTION

DATE

ECO

APPR

A

RELEASE TO MFG.

24-Jun-16

01022

RS

Ø15.9 REF.

Ø15.9mm CLEARANCE
SCALE 4.000

HEAT SHRINK TUBING

FEMALE CONTACT

FERRULE

BODY SUB-ASSEMBLY

O-RING

HOUSING

Ø8 REF.

Ø1 REF.

Ø3.86 REF.

Ø2.7 REF. (OVER KNURL)

19 REF.

11.43 REF. CONTACT SHOWN FOR REFERENCE ONLY

9.52 REF.

24.15 REF.

23 REF.

35.49 REF. (AFTER ASSEMBLY)

CODING	DRAWING NO.	COLOR	RAL NO.
A	3FAIENASJ-COIES	JET BLACK	9005
B	3FAIENBSJ-COIES	CREAM	9001
C	3FAIENCSJ-COIES	SIGNAL BLUE	5005
D	3FAIENDSJ-COIES	CLARET VIOLET	4004
E	3FAIENESJ-COIES	LEAF GREEN	6002
F	3FAIENFSJ-COIES	NUT BROWN	8011
G	3FAIENG SJ-COIES	BLUE GREY	7031
H	3FAIENHSJ-COIES	HEATHER VIOLET	4003
I	3FAIENISJ-COIES	BEIGE	1001
K	3FAIENKSJ-COIES	CURRY	1027
L	3FAIENLSJ-COIES	CARMINE RED	3002
M	3FAIENMSJ-COIES	PASTEL ORANGE	2003
N	3FAIENNSJ-COIES	PASTEL GREEN	6019
Z	3FAIENZSJ-COIES	WATER BLUE	5021

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE:
<0.5mm 0.5 - 6mm 6 - 30mm 30 - 120mm ANGLES
± 0.05mm ±0.1mm ±0.2mm ± 0.3mm ±1°

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the finishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other sperson to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

MATERIAL	DRAWN	DATE	TITLE		Amphenol RF	
-	H.CHEN	24-Jun-16	GEN 3.5 FAKRA JACK, COI CABLE GROUP, IP67 SEALED TAPE AND REEL CONTACT (SUPPLIED SEPARATELY)		Danbury CT USA, Tainan, Taiwan, Shenzhen, China www.amphenolrf.com	
REFERENCE EAR # 6633 AND	ENGINEER E.WANKOFF	DATE 24-Jun-16	APPROVED S.HSIEH		DRAWING NO.3FAIENXSJ-COIES	
CONFIGURATION LEVEL: RELEASE	CAD FILE	DATE 24-Jun-16	SCALE: 3.0:1.0 SHEET 2 OF 2		ITEM NO. 3FAIENXSJ-COIES	
FINISH			DWG SIZE B REV A		PART NO. 3FAIENXSJ-COIES	

CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY