





REV.	DATE	DESCRIPTION
NC	08/05/99	INITIAL RELEASE
A	07/20/05	UPDATE DRAWING FORMAT



RECOMMENDED
CABLE STRIPPING DIM'S



					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007" .315 – 1.180 = ± 0.015" 1.180 – 4.724 = ± 0.020" DO NOT SCALE DRAWING	APPROVALS	DATE	Amphenol Connex				
8						DRAWN	G.R.S.					07/20/05
7						CHECKED			PART DESCRIPTION TNC CRIMP JACK – REVERSE POLARIZED (FOR RG-8X, TIMES LMR-240 CABLE)			
6						ISSUED						
5						SHEET	1 OF 1		PART NO. 122409RP			
4	FERRULE	COPPER	NICKEL	1								
3	CONTACT PIN	PHOS. BRONZE	GOLD	1				DWG. NO. 122409RP.DWG				
2	INSULATOR	TEFLON	NATURAL	1								
1	BODY	BRASS	NICKEL	1				REV. A	SIZE A	SCALE NA		
	DESCRIPTION	MATERIAL	FINISH	QTY								