

Analog or Digital Triple Output DC Power Supply



Adjustable 30V/3A

With fixed 5V and 12V outputs

Features:

- 382203 - Analog display
382213 - Digital LCD display
- Triple Output: Adjustable 0-30V, 0-3A plus fixed 5V and 12V
- 0-30V Adjustable Voltage Output
- 0-3A Adjustable Current Output
- Independent 5V and 12V Outputs Provide Power for TTL or CMOS Projects
- Easy Snap Terminals for 5V and 12V outputs
- Overload and Short Circuit Protection
- Constant Voltage or Current
- Current Limiting Front Panel LED Indicator
- Binding Post Terminals for Variable Supply
- Complete with power cord



Specifications

Voltage Output, DC	0 to 30 Volts
Current Output, DC	0 to 3 Amps
Ripple and Noise	<5mV
Line Regulation	<0.05%+10mV
Load Regulation	<0.05%+10mV
Fixed Output Voltage	5V/0.5A (cont.), 1A(max); 12V/0.5A (cont.), 1A(max)
Display	382203 - Analog or 382213 - Digital (V&A), 3 digit 0.1 res. LCD
Power	110/220VAC 50/60Hz
Dimensions	6 x 5.6 x 9.5" (152 x 142 x 242)
Weight	11lbs. (5kg)

Ordering Information:

- 382203 Analog DC Power Supply, 115/220 VAC
 382203-NIST Analog DC Power Supply, 115/220 VAC with Calibration Traceable to NIST.
 382213 Digital DC Power Supply, 115/220 VAC
 382213-NIST Digital DC Power Supply, 115/220 VAC with Calibration Traceable to NIST.

