

UEK

Grounding Kits

GROUNDING KITS
PRODUCT CATALOGUE



CERTIFICATION

IEC 60529	Waterproof IP 67
IEC 61312-1 grade III	CESI
Temperature Range	-50°/+80°C
Contact Resistance	<1 mOhm

MATERIAL

Contact Bar	Tinned Brass
Internal Contact	Tinned Copper Mesh
Protection	NAS Black Self-Agglomerating Tape, U.V. Resistant
Cable**	16 mm ² Copper, P.E. Insulated Black, According to CEI 20-22
Colour	Black

UEK - Universal Earthing Kit

For coaxial cables and elliptic or rectangular waveguides.
Only five items for the whole cable range.
Easy to handle, safe, quick to install.
Complete with connecting cable.

UEK - Kit di Messa a Terra Universale

*Per cavi coassiali e guide d'onda ellittiche e rettangolari. Solo cinque misure per tutta la gamma di cavi.
Semplice, sicuro, veloce.
Completo di cavo di connessione.*

CODE	ARTICLE	CABLE Ø	COAX CABLES	ELLIPT. GUIDES	**L	CONNECTING SCREW	BAG	BOX	WEIGHT
61 1502 0001	UEK 1	5 - 11	RG 223 - RG58-RG59 RG 8 - RG213/214 1/4" - 3/8"	220-380	500	M8	1	10	145
61 1502 0002	UEK 2	12 - 30	1/2"S - 3/8" - 1/2" - 5/8" 7/8"S - 7/8"	105-127-130 150-190	500	M8	1	10	180
61 1502 0003	UEK 3	31 - 60	1.1/4" - 1.5/8" - 2.1/4"	38-46-48-54 60-70-77-78-90	500	M8	1	10	210
61 1502 0004	UEK 4	40 - 115	1.1/4" - 1.5/8" 2.1/4" - 3"; 3.1/8" - 4.1/8"	38-46-48-54	500	M8	1	10	275
61 1502 0005	UEK 5	40 - 223	1.1/4" - 1.5/8"; 2.1/4"- 3" 2.1/4"- 3"; 3.1/8" - 4.1/8" -5"; 6.1/8" - 8"	11-15-19-22 38-46-48-54	500	M8	1	10	350

Storage : UEK kit does not require a particular care in storing, apart from keeping it in its original packing, which protects it from water, grease and dust. Even extreme temperature conditions do not negatively affect the product.