


ROHS COMPLIANT		PRODUCT DATA DRAWING		REVISION HISTORY			
				REV	DESCRIPTION	DATE	APPROVED
				-	DCN 40314	01/14	STW

ROHS COMPLIANT		REVISION HISTORY			
		REV	DESCRIPTION	DATE	APPROVED
		-	DCN 40314	01/14	STW

		ATTENUATION ACCURACY (+/-)		
M3933/30-XX	dB VALUE	DC-26.5 GHz	26.5-32.0 GHz	DC-32.0 GHz
01	0	-	-	0.5/0
02	0.5	-	-	0.5
03	1	-	-	0.5
04	1.5	-	-	0.5
05	2	-	-	0.5
06	2.5	-	-	0.5
07	3	-	-	0.5
08	3.5	-	-	0.5
09	4	-	-	0.5
10	4.5	-	-	0.5
11	5	-	-	0.5
12	5.5	-	-	0.5
13	6	-	-	0.5
14	6.5	-	-	0.5
15	7	-	-	0.5
16	7.5	-	-	0.5
17	8	-	-	0.5
18	8.5	-	-	0.5
19	9	-	-	0.5
20	9.5	-	-	0.5
21	10	-	-	0.5
22	10.5	-	-	0.5
23	11	-	-	0.5
24	11.5	-	-	0.5
25	12	-	-	0.5
26	13	0.8	1	-
27	14	0.8	1	-
28	15	0.8	1	-
29	16	0.8	1	-
30	17	0.8	1	-
31	18	0.8	1	-
32	19	0.8	1	-
33	20	0.8	1	-
34	25	1	1.5	-
35	30	1	1.5	-

MATERIAL: SEE NOTES		DIMENSIONS ARE IN INCHES TOLERANCES:		UNLESS OTHERWISE SPECIFIED		SV Microwave, Inc. 2400 Centrepark West Drive, Suite 100 West Palm Beach, FL 33409			
FINISH: SEE NOTES		FRACTIONAL: ±1/64 ANGULAR: X° ±1°0' X°X' ±15'		DECIMAL: .X ±.030 .XX ±.010 .XXX ±.005					
SURFACE AREA: N/A		INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994		1) ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) 2) ALL DIMENSIONS ARE AFTER PLATING. 3) BREAK CORNERS & EDGES .005 R. MAX. 4) CHAM. 1ST & LAST THREADS. 5) SURFACE ROUGHNESS 63-MIL-STD-10. 6) DIA.'S ON COMMON CENTERS TO BE CONCENTRIC WITHIN .005 T.I.R. 7) REMOVE ALL BURRS		TITLE: SVK JACK TO SVK PLUG DC-32 GHz ATTENUATOR			
PROPRIETARY THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SV MICROWAVE, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SV MICROWAVE, INC IS PROHIBITED.		THIRD ANGLE PROJECTION		DRAWN: JMC 12/23/13		SIZE B	CAGE CODE 95077	DWG. NO. M3933/30-XX	
				CHECKED:					
				APPROVED:		SCALE: 4:1			
								SHEET 2 OF 2	