

Product Specifications

COMMSCOPE®



F4R-DMDM-2M-D

D-CLASS FSJ4RK-50B SureFlex® Jumper with interface types 7-16 DIN Male and 7-16 DIN Male, 2 m

Logo Image



Product Classification

Product Series	FSJ4-50B
Product Type	SureFlex® D-CLASS, dynamic PIM

General Specifications

Body Style, Connector A	Straight
Body Style, Connector B	Straight
Cable Family	FSJ4-50B
Interface, Connector A	7-16 DIN Male
Interface, Connector B	7-16 DIN Male
Length	2.000 m 6.562 ft
Nominal Size	1/2 in
Specification Sheet Revision Level	A

Electrical Specifications

3rd Order IMD Dynamic	-159.00 dBc -116.00 dBm
3rd Order IMD Dynamic Test Method	Two +43 dBm carriers per IEC 62037
DTF, Connector A	-34.00 dB
DTF, Connector B	-34.00 dB

Jumper Assembly Sample Label

Product Specifications

COMMScope®

F4R-DMDM-2M-D



Return Loss/VSWR

Frequency Band	VSWR	Return Loss (dB)
698–960 MHz	1.06	30.00
1700–2200 MHz	1.06	30.00
2200–2700 MHz	1.11	26.00

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant by Exemption
China RoHS SJ/T 11364-2006	Above Maximum Concentration Value (MCV)
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

