






NOTES:

1. IMPEDANCE: 75 OHM
2. FREQUENCY RANGE: DC - 6 GHz
3. VSWR: 1.1 MAX
4. DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS, MIN.
5. CRIMPED FERRULE
HEX.CRIMP SIZE 0.278"
6. CRIMPED CONTACT PIN
HEX.CRIMP SIZE 0.041" OR 0.042"



SCALE 1.500

10	FERRULE	BRASS	NICKEL	1
9	CONTACT PIN	BRASS	GOLD	1
8	RING	BRASS	NICKEL	1
7	WASHER	BRASS	NICKEL	1
6	SPRING	SK5	NICKEL	1
5	GASKET	RUBBER	RED	1
4	OUTER CONTACT	BERYLLIUM COPPER	NICKEL	1
3	INSULATOR	PTFE	NATURAL	1
2	BODY	BRASS	NICKEL	1
1	SHELL	BRASS	NICKEL	1
S.NO	DESCRIPTION	MATERIAL	FINISH	QTY.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL ±.015 (0,381 mm) ±.005 (0,127 mm) ANGLES ± 1°	MATERIAL	DRAWN	DATE	TITLE BNC CRIMP PLUG - 75 OHM FOR BELDEN 1694A AND GEPCO VSD2001 CABLE	Amphenol Connex		
		CLEMENT	25-Apr-13				
	REFERENCE	ENGINEER	DATE				
		CLEMENT	25-Apr-13				
NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	SEE BOM TABLE		APPROVED	DATE	SCALE: 4.0:1 SHEET 1 OF 1		
	CAD FILE		DWG SIZE		DRAWING NO.	REV	
		B		112957-11		E	