


CGK M PAT.

Compact Grounding Kits

GROUNDING KITS
PRODUCT CATALOGUE



CGK M ◀
Open

CGK M ◀
Closed



MATERIAL	
Shell	AISI 304 Stainless Steel
Gasket	EPDM Rubber U.V. Resistant
Inner Contact	Tinned Brass
Cable**	16 mm ² Copper, Black PVC Insulated, Conforming to CEI 20-22 Norms (yellow/green on request)
Lug	Tinned Copper, ø 8 hole (ø10 on request)

CERTIFICATION	
IEC 60529	Waterproof IP 68
Enviromental Test	IEC 68-2-14
Contact Resistance	<1 mOhm
Corrision Resistent	✓

CGK M - Compact Monobloc Grounding Kit
For Copper or Aluminum RF Coaxial Cables.
Parallel Cable Exit

Technical features:

- Compact structure
- Fast and easy installation
- Closure with pressure plate
- Flexible metal shell
- No loose parts
- No extra taping needed

CGK M - Kit di Terra Monoblocco Compatto
Per Cavi Coassiali RF, in Rame o Alluminio.
Uscita Parallela

Caratteristiche:

- Struttura compatta
- Installazione veloce
- Chiusura con piastrino
- Guscio metallico deformabile
- Senza parti sciolte
- Nastratura supplementare non necessaria

CODE	ARTICLE	FOR COAXIAL CABLES	øD	**L	BOX	WEIGHT
61 1509 0016	CGK 1/2" S M	ø d 13-14 (1/2" superflex)	24	500	10	161
61 1509 0012	CGK 1/2" M	ø d 16-17 (1/2")	24	500	10	161
61 1509 0078	CGK 7/8" M	ø d 26-28 (7/8" + 7/8" superflex)	35	500	10	166
61 1509 0114	CGK 1.1/4" M	ø d 38-40 (1.1/4")	47	500	10	179
61 1509 0158	CGK 1.5/8" M	ø d 50-52 (1.5/8")	57	500	10	208