

SFP-10G-SR

Cisco

IntegraOptics' SFP+ transceivers are designed in accordance to industry standards and are available in a variety of power budgets and data rate options. Integra SFP+ transceivers are coded to be 100% OEM compatible and provide for reliable, versatile, cost effective 10G service deployments capable of meeting both current and future networking requirements.

Features

- Operating Data Rate up to 11.1Gbps
- 300m Reach
- MMF Duplex LC Connector Interface
- Commercial, Extended & Industrial Temperatures Available
- Digital Diagnostics Monitoring (SFF-8472)
- Meets MSA SFF-8431



Applications

- 10GBase-SR
- Enterprise & Data Center Networks

Product Specifications

Part Number	Wavelength (nm)	Distance (km)	Power Budget (dB)	Interface
SFP-10G-SR	850nm	300m	5.1dB	LC/MMF

SFP-10G-SR

Detailed Specifications

Parameter	Minimum	Typical	Maximum	Unit
Storage Temperature (Ts)	-40	-	85	°C
Operating Case Temperature CTemp (Tc)	0	-	70	°C
Operating Case Temperature ITemp (Tc)	-10	-	85	°C
Power Supply Voltage (Vcc)	-	3.3	-	V
Power Supply Current (Icc)	-	-	300	mA

Transmitter

Parameter	Minimum	Typical	Maximum	Unit
Center Wavelength (λ_C)	840	850	860	Nm
Data Rate	-	10.3125	-	Gbps
Spectral Width (-20dB) ($\Delta\lambda$)	-	-	0.45	nm
Average Output Power (Pout, AVG)	-6	-	-1	dBm
Extinction Ratio (ER)	3.0	-	-	dB

Receiver

Parameter	Minimum	Typical	Maximum	Unit
Center Wavelength (λ_C)	840	850	860	nm
Receiver Sensitivity (PIN)	-	-	-11.1	dBm
Receiver Overload (P _{MAX})	-1	-	-	dBm

Warranty Information

The IntegraOptics' SFP+ 10G is covered by the standard IntegraOptics warranty. Please contact an IntegraOptics sales representative for additional details.