

NOTES:

1. MATERIALS AND FINISHES:

BODY - BRASS, NICKEL PLATING (.000100" MIN. THICK)
HOUSING - BRASS, MATTE-TIN PLATING (.000100" MIN. THICK)
CONTACT - BeCu, GOLD PLATING (.000003" MIN. THICK)
INSULATOR - PTFE, NATURAL

2. ELECTRICAL:

A. IMPEDANCE: 50 OHM
B. FREQUENCY RANGE: DC - 6 GHz
C. D.W.V: 1000 VRMS, MIN.


3. MECHANICAL:

A. DURABILITY: 500 CYCLES MIN.
B. TEMPERATURE RANGE: -65°C TO +165°C

THIRD ANGLE PROJ.




REVISIONS

REV	DESCRIPTION	DATE	ECO	APPR
A	RELEASE TO MFG.	04-Jul-16	01326	MZ



SCALE 4.000

INTERFACE PER
CECC 22000
SERIES: MCX JACK



RECOMMENDED
PCB MOUNTING HOLE

CUSTOMER OUTLINE DRAWING
ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE: <0.5mm ± 0.05mm 0.5 - 6mm ±0.1mm 6 - 30mm ±0.2mm 30 - 120mm ± 0.3mm ANGLES ±1° NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	MATERIAL -	DRAWN M. ZHANG	DATE 04-Jul-16	TITLE MCX R/A P.C. BOARD RECEPT. JACK (3.94 LEGS - MATTE TIN)	Amphenol RF www.amphenolrf.com	
		ENGINEER S. DUAN	DATE 04-Jul-16			
		REFERENCE SAME AS MCX6252B1-3GT30G-50 EXCEPT PLATING CONFIGURATION LEVEL: In Work	DATE 06-Jul-16		DRAWING NO. 919-383J-51A	
		CAD FILE			ITEM NO. 919-383J-51A	
		FINISH			PART NO. 919-383J-51A	