

NOTES:


1. MATERIALS AND FINISHES:
BODY - BRASS, NICKEL PLATING
CONTACT - PHOSPHOR BRONZE, GOLD PLATING
INSULATOR - PTFE, NATURAL
2. ELECTRICAL:
A. IMPEDANCE: 50 OHM
B. FREQUENCY RANGE: DC - 11 GHz
C. DIELECTRIC WITHSTANDING VOLTAGE: 2500 VRMS, MIN.
3. MECHANICAL:
A. DURABILITY: 500 CYCLES MIN.
B. TEMPERATURE RANGE: -65° C TO +165° C
4. THIS CONNECTOR IS COVERED BY U.S. P. PATENT 3, 439, 294 & 3, 474, 391
5. PACKAGING:
A. QUANTITY: SINGLE PACK
B. MARKING: BAG TO BE MARKED
"AMPHENOL RF, 82-5374, AND DATE CODE"
6. CABLE ASSEMBLY INSTRUCTIONS:
A. TRIM CABLE AS SHOWN.
B. SLIDE FERRULE ONTO THE CABLE.
C. CRIMP OR SOLDER CABLE CENTER CONDUCTOR TO CENTER CONTACT.
CRIMP CONTACT PIN TO CABLE WITH AMPHENOL TOOL 227-944 AND DIE SET 227-1221-57, CLOSURE 'B' (0.100" HEX)
D. INSERT CENTER CONTACT INTO CONNECTOR WITH BRAID OVER THE REAR BODY AND CRIMP FERRULE WITH AMPHENOL TOOL 227-944, (M22520/5-01) AND DIE SET 227-1221-57, CAVITY 'A' (0.213" HEX) (M22520/5-57, CLOSURE 'A').

7 SHOWS CABLE ENTRY DIMENSIONS.

THIRD ANGLE PROJ.


REVISIONS

REV	DESCRIPTION	DATE	ECO	APPR
C	SEE SHEET 1	02-Dec-04	--	SH
T	SEE SHEET 1	24-Aug-09	47747	SH
U	REDRAWN IN PRO-E	29-May-15	49810	RAK
V	SEE SHEET 1	16-Jun-16	01162	BC



RECOMMENDED CABLE STRIPPING DIMENSIONS





INTERFACE PER
349-50551, SEC-304
SERIES : N PLUG



SCALE 1:100

STAMP "AMPHENOL 82-5374"

AMPHENOL 82-5374



UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE:
<0.5mm ± 0.05mm 0.5 - 6mm ± 0.1mm 6 - 30mm ± 0.2mm 30 - 120mm ± 0.3mm ANGLES ± 1°

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

MATERIAL
SEE NOTES

REFERENCE
EPA 802145-51
MOTOROLA 28009835F02
EAR 964616-0

FINISH

DRAWN STAR	DATE 16-Jun-16
ENGINEER S.HSIEH	DATE 02-Dec-04
APPROVED S.HSIEH	DATE 16-Jun-16
CAD FILE	

TITLE
QUICK CRIMP 'N' RIGHT ANGLE
PLUG FOR RG55/U,55A/U,55B/U
142/U,142B/U,223/U CABLES

SCALE: 3.8:1.0	SHEET 2 OF 2
DWG SIZE B	REV V

Amphenol RF

www.amphenolrf.com

DRAWING NO.82-5374

ITEM NO.82-5374

PART NO.82-5374