

5

4

3

2

1

NOTES:

1. MATERIALS AND FINISHES:
RP TNC STR PLUG - BRASS, NICKEL PLATING
RP TNC STR JACK - BRASS, NICKEL PLATING
CABLE - LMR 400

2. ELECTRICAL:
A. IMPEDANCE: 50 OHM

3. PACKAGING:
A. QUANTITY: SINGLE PACK
B. MARKING: BAG TO BE MARKED
"AMPHENOL RF, 95-850-230-XXX AND DATE CODE"

REVDESCRIPTIONDATEECNAPPR
ARELEASE TO MFG.24-JUN-2015247EH

SCALE 0.400

LENGTH 'L' (SEE TABLE)

0.622 HEX
[14.85]

HEAT SHRINK TUBE
TYP(2)

1.000 REF
[25.40]
TYP(2)

9/16" WRENCH

7/16-28UNEF-2A
THREAD

INTERFACE PER
RP TNC JACK

INTERFACE PER
RP TNC PLUG

LENGTH TABLE

PART NUMBER (IMPERIAL)	PART NUMBER (METRIC)	LENGTH 'L' IN INCHES [METERS]
95-850-230-012	-	12.00 [0.305]
95-850-230-024	-	24.00 [0.610]
95-850-230-036	-	36.00 [0.914]
-	95-850-230M100	39.37 [1.000]
95-850-230-048	-	48.00 [1.219]
95-850-230-072	-	72.00 [1.829]
-	95-850-230M200	78.74 [2.000]
-	95-850-230M300	118.11 [3.000]
-	95-850-230M400	157.48 [4.000]

TOLERANCE TABLE

LENGTH IN INCHES/FT [METERS]	TOLERANCE
0" - 23.90" [0 - 0.607]	±0.25" [0.006]
24.00" - 59.00" [0.610 - 1.499]	±0.50" [0.013]
5.0' - 24.9' [1.524 - 7.617]	±2.5%
25.0' & UP [7.620 & UP]	±5.0%

DESIGN REQUIREMENTS:

☒ FREQUENCY: DC - 8 GHz

☒ CONTINUITY

☐ VSWR: ____ 1 MAX.

☒ HI-POT: 750 VRMS

☐ INS. LOSS: ____ dB MAX.

☐ OTHER

NOTICE: These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

THIRD ANGLE PROJ.

REFERENCE

EAR#
EAR # 9189

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE METRIC [INCHES] AND TOLERANCES ARE:
<0.5mm = ±0.05mm [$<0.020 = \pm0.002$]
>0.5 - 6mm = ±0.1mm [$>0.020 - 0.236 = \pm0.004$]
>6.00 - 30mm = ±0.2mm [$>0.236 - 1.181 = \pm0.008$]
>30.00 - 120mm = ±0.3mm [$>1.181 - 4.725 = \pm0.012$]

ANGLES = ±1°

MATERIAL

ENGINEER
KARTHIK R

DATE
14-MAY-20

TITLE
RP TNC STR PLUG TO
RP TNC STR JACK
USING LMR 400 CABLE
VARIOUS LENGTH

SHEET NO. 2 OF 2

SCALE: 1.4:1.0

Amphenol RF

SIZE
B

DRAWING NO. 95-850-230-XXX
ITEM NO. 95-850-230-XXX
PART NO. 95-850-230-XXX

REV
A

5

4

3

2

1

Downloaded from Arrow.com