

Coaxial Cable Connector  
16\_QMA-50-3-1/133\_N

Description

Right angle cable plug

Interface standards  
QMA QLF compliant



Technical Data

Electrical Data

Impedance 50 Ω  
Interface frequency max. 18 GHz

Mechanical Data

Centre contact soldered  
Outer contact crimped  
Weight 0.0081 kg

Environmental Data

Operating temperature -40 °C to 85 °C  
2011/65/EU (RoHS - including  
2015/863 and 2017/2102) compliant

Material Data

| Piece Parts    | Material   | Surface Plating       |
|----------------|------------|-----------------------|
| Centre contact | Brass      | SUCOPRO Plating       |
| Outer contact  | Bronze     | SUCOPLATE (R) Plating |
| Body           | Brass      | SUCOPLATE (R) Plating |
| Insulator      | PFA / PTFE |                       |
| Crimp ferrule  | Copper     | SUCOPLATE (R) Plating |

Related Documents

Outline drawing DOU-00005830  
Catalogue drawing DOU-00005832  
Assembly instruction DOC-0000178735

Ordering Information

Bulk 100 pcs package 16\_QMA-50-3-1/133\_NH  
Single package 16\_QMA-50-3-1/133\_NE

Additional Information

Suitable cables RG\_400\_/U, RG\_223\_/U, ENVIROFLEX\_400, RADOX\_RF\_400, ENVIROFLEX\_142, RADOX\_RF\_142