



1. CONTACT PIN TO SOLDER

					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007” .315 – 1.180 = ± 0.015” 1.180 – 4.724 = ± 0.020” DO NOT SCALE DRAWING	APPROVALS		DATE		Amphenol Connex											
8						DRAWN	G.R.S.	01/28/03								PART DESCRIPTION MMCX STRAIGHT DIRECT SOLDER PLUG (FOR .034.” SEMI-RIGID CABLE)					
7						CHECKED															
6						ISSUED				PART NO. 262134											
5	SOLDER BARREL	BRASS	GOLD	1		SHEET	1 OF 1														
4	INSULATOR	TEFLON	NATURAL	1																	
3	CONTACT PIN	BER. COPPER	GOLD	1																	
2	INSULATOR	TEFLON	NATURAL	1																	
1	BODY	BRASS	GOLD	1																	
	DESCRIPTION	MATERIAL	FINISH	QTY		CAD FILE C:/262/262134.DWG		DWG. NO.			262134.DWG		REV.	NC	SIZE	A	SCALE	NA			