



1. CRIMPED FERRULE HEX CRIMP SIZE .151" [3.83]
2. CONTACT PIN TO SOLDER
3. MAX. PANEL THICKNESS = 6.8mm

					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007" .315 – 1.180 = ± 0.015" 1.180 – 4.724 = ± 0.020" DO NOT SCALE DRAWING	APPROVALS	DATE	Amphenol Connex						
8						DRAWN	GRS						11/08/08	
7	FERRULE	COPPER	GOLD	1		CHECKED								
6	HEX NUT	BRASS	GOLD	1		ISSUED			PART DESCRIPTION MCX BULKHEAD CRIMP JACK (FOR RG316/U DOUBLE BRAID CABLE)					
5	LOCK WASHER	BRASS	GOLD	1		SHEET	1 OF 1							
4	CONTACT PIN	BER. COPPER	GOLD	1					PART NO. 252147					
3	BARREL	BRASS	GOLD	1										
2	INSULATOR	PTFE	NATURAL	2		CAD FILE			DWG. NO. 252147.DWG REV. B SIZE A SCALE NA					
1	BODY	BRASS	GOLD	1	C:/252/252147.DWG									
	DESCRIPTION	MATERIAL	FINISH	QTY										