

5

4

3

2

1

NOTES:

1. MATERIALS AND FINISHES:
N STR PLUG - BRASS, WHITE BRONZE PLATING
N RA PLUG - BRASS, NICKEL PLATING
CABLE - LMR 240

2. ELECTRICAL:
A. IMPEDANCE: 50 OHM

3. PACKAGING:
A. QUANTITY: SINGLE PACK
B. MARKING: BAG TO BE MARKED
"AMPHENOL RF, 95-909-186-XXX AND DATE CODE"

REVDESCRIPTIONDATEECNAPPR

ARELEASE TO MFG.18-NOV-2015409MR

SCALE 0.300

LENGTH 'L' (SEE TABLE)

HEAT SHRINK TUBE
TYP(2)

25.40±1.27
[1.000±0.050]
TYP(2)

INTERFACE PER
MIL-STD-348
SERIES: N PLUG
TYP(2)

LENGTH TABLE

PART NUMBER (IMPERIAL)	PART NUMBER (METRIC)	LENGTH 'L' IN INCHES [METERS]
95-909-186-006	-	6.00 [0.152]
	95-909-186M025	9.84 [0.250]
95-909-186-012	-	12.00 [0.305]
95-909-186-018	-	18.00 [0.457]
-	95-909-186M050	19.69 [0.500]
95-909-186-024	-	24.00 [0.610]
95-909-186-036	-	36.00 [0.914]
-	95-909-186M100	39.37 [1.000]
95-909-186-048	-	48.00 [1.219]

TOLERANCE TABLE

LENGTH IN INCHES/FT [METERS]	TOLERANCE
0" - 23.90" [0 - 0.607]	±0.25" [0.006]
24.00" - 59.00" [0.610 - 1.499]	±0.50" [0.013]
5.0' - 24.9' [1.524 - 7.617]	±2.5%
25.0' & UP [7.620 & UP]	±5.0%

DESIGN REQUIREMENTS:

☒ FREQUENCY: DC - 6 GHz

☒ CONTINUITY

☐ VSWR: ____ 1 MAX.

☒ HI-POT: 1000 VRMS

☐ INS. LOSS: ____ dB MAX.

☐ OTHER

NOTICE: These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

THIRD ANGLE PROJ.REFERENCE

EAR#
10174

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE METRIC [INCHES] AND TOLERANCES ARE:
<0.5mm = ±0.05mm [≤0.020 = ±0.002]
>0.5 - 6mm = ±0.1mm [>0.020 - 0.236 = ±0.004]
>6.00 - 30mm = ±0.2mm [≥0.236 - 1.181 = ±0.008]
>30.00 - 120mm = ±0.3mm [≥1.181 - 4.725 = ±0.012]

ANGLES = ±1°

MATERIAL

SEE NOTES

ENGINEER
MADHAN G

DATE
08-OCT-20

TITLE
N STR PLUG TO
N RA PLUG
USING LMR 240 CABLE
VARIOUS LENGTH

SHEET NO. 2 OF 2

SCALE: 2.0:1.0

Amphenol RF

SIZE
B

DRAWING NO. 95-909-186-XXX
ITEM NO. 95-909-186-XXX
PART NO. 95-909-186-XXX

REV
A

5

4

3

2

1

Downloaded from Arrow.com