

NOTES:

1. MATERIALS AND FINISHES:

BODY, LOCKWASHER & HEX NUT - BRASS (ASTM-B16 H02, C36000), NICKEL PLATING
CONTACT PIN - PHOSPHOR BRONZE, GOLD PLATING
INSULATOR - PTFE PER ASTM D 1710 OR EQUIV.
GASKET - SILICONE RUBBER, RED
FERRULE - COPPER, NICKEL PLATING

2. ELECTRICAL:

A. IMPEDANCE: 50 OHM
B. FREQUENCY RANGE: DC - 11 GHz

3. MECHANICAL:

A. TEMPERATURE RANGE: -65° C TO +165° C


4. PACKAGING:

A. QUANTITY: SINGLE PACK
B. MARKING: BAG TO BE MARKED
*AMPHENOL, 31-6169, AND DATE CODE


5. CRIMPED FERRULE = HEX CRIMP SIZE .213 IN
CRIMPED CONTACT PIN = HEX CRIMP SIZE .068 IN

6. MAX PANEL THICKNESS = 3.5mm



DRAWING NO.		REV				REVISIONS		
THIRD ANGLE PROJ.		A		RELEASE TO MFG.		DATE	ECO	APPR
31-6169		A		RELEASE TO MFG.		8/29/06	46223	CPM/



RECOMMENDED CABLE
STRIPPING DIMENSIONS



RECOMMENDED
MOUNTING HOLE



UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:
2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES
±.015 (0,381 mm) ±.005 (0,127 mm) ± 1°

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

MATERIAL

REFERENCE

DRAWN

ENGINEER

APPROVED

DATE

DATE

DATE

TITLE

TNC BULKHEAD CRIMP
JACK (FOR RG-142/U,
223/U, 400/U CABLE)

Amphenol

Amphenol Corporation
RF/Microwave Operations
Danbury, Conn. U.S.A. 06810

SCALE: 2:1 SHEET OF

CODE ID
74868

DWG SIZE
B

DRAWING NO.
31-6169

ISSUE
A