

164 Series

Amphenol

Waterproof Audio Connectors



Amphenol

Introduction


Amphenol 164 Series connectors are waterproof, polarised, five and six contact electrical connectors, for use in low voltage audio frequency circuits and applications. They employ three-point bayonet coupling for quick disconnect and self-wipe contact action. Although designed for use in communications equipment, these versatile connectors have been successfully adapted for use in numerous industrial, scientific and educational applications.

Amphenol 164 Series connectors are designed to meet the requirements of **MIL-C-55116**. They are intermateable and interchangeable with all MIL-C-55116 connectors.

Specifications


Number of Contacts	5 or 6
Operating Temperature	-55°C to +85°C
Operating Current	500 mA per contact
Operating Voltage	60 V max
Contact Resistance	$\leq 40\Omega$
Insulation Resistance	$\leq 1000\text{ M}\Omega$ @ 100 V DC
Voltage Proof	500Vrms
Sealing	0.17 kg/cm ²
Materials :	Insulator : DAP
	Contact : Brass
	Shell : Stainless Steel
Finish:	Contact : 1.25 μm gold over nickel on mating contact
	Shell : Sand blasted and passivated

Receptacles



Part Number	No. of Contacts	Contact Type	Mates with
164-183	5	Solder Spring Loaded	164-229 164-229-S 164-182
164-183P	5	PC Tail Spring Loaded	164-182-S 164-182-L 164-182-LS
164-183-6	6	Solder Spring Loaded	164-229-6 164-229-6S 164-182-6
164-183-6P	6	PC Tail Spring Loaded	164-182-6S 164-182-6L


Plugs



Part Number	No. of Contacts	Contact Type	Mates with
164-229	5	Barrel – Rigid	164-183 164-183-P
164-229-S	5	Solder – Rigid	
164-182	5	Barrel – Rigid	
164-182-S	5	Solder – Rigid	
164-182-L	5	Barrel – Rigid	
164-182-LS	5	Solder – Rigid	
164-229-6	6	Barrel – Rigid	164-183-6 164-183-6P
164-229-6S	6	Solder – Rigid	
164-182-6	6	Barrel – Rigid	
164-182-6S	6	Solder – Rigid	
164-182-6L	6	Barrel – Rigid	
164-182-6LS	6	Solder – Rigid	

Note: 1) denotes lightweight version

Cable Receptacles




All dimensions in mm

Part Number	No. of Contacts	Contact Type	Mates with
164-228	5	Barrel Spring Loaded	164-229 164-229-S 164-182 164-182-S 164-182-L 164-182-LS
164-228-S	5	Solder Spring Loaded	
164-228-6	6	Barrel Spring Loaded	164-229-6 164-229-6S 164-182-6 164-182-6S 164-182-6L
164-228-6S	6	Solder Spring Loaded	

Accessories

Cap and Chain

These cap and chain assemblies are used with 5 and 6 pin connectors as protective covers giving additional protection against moisture, dust and sand. The caps are manufactured from aluminium and black anodised. The chain is manufactured from stainless steel and is passivated.




All dimensions in mm

Part Number	For Connector
164-895	164-183
164-896	164-229

Cap and Chain

For ten pin waterproof audio receptacles (U-79/U) Part No. 164-377



Note: Products are sold subject to Amphenol's conditions of sale ("the standard conditions"). All specifications and statements contained herein are believed to be correct at the time of printing but no representation or warranty, express or implied, is given as to any specification or statement contained herein. Product specifications including performance characteristics are typical only and subject to deviation. Specifications are also subject to change without notice. Users should not assume that all safety measures are indicated or that other measures may not be required. No representation or warranty, express or implied, is given that any use of products (including any stated or suggested use) does not infringe any patent, registered design or other third party rights and no stated or suggested use of products can be taken to recommend any such infringement.

Amphenol

Thanet Way, Whitstable, Kent. CT5 3JF. Tel: 01227 773200 Fax: 01227 276571