

1. MATERIALS AND FINISHES:
CONNECTOR A: 112132- STR BNC CRIMP PLUG
CONNECTOR B: 112160- STR BNC CRIMP JACK
CABLE: RG-316

3. MECHANICAL:
A. TEMPERATURE RANGE: -55° C TO 165° C

SCALE 0.500

NOTICE: These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.			UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE METRIC [INCHES] AND TOLERANCES ARE: <0.5mm = $\pm 0.05\text{mm}$ [$<0.020 = \pm 0.002$] >0.5 - 6mm = $\pm 0.1\text{mm}$ [$>0.020 - 0.236 = \pm 0.004$] >6.00 - 30mm = $\pm 0.2\text{mm}$ [$>0.236 - 1.181 = \pm 0.008$] >30.00 - 120mm = $\pm 0.3\text{mm}$ [$>1.181 - 4.725 = \pm 0.012$]			MATERIAL BNC STR PLUG TO BNC STR JACK RG-316, VARIOUS LENGTHS		TITLE BNC STR PLUG TO BNC STR JACK RG-316, VARIOUS LENGTHS			Amphenol RF		
THIRD ANGLE PROJ. 			REFERENCE ---			DATE 1/31/2021		SIZE B		DRAWING NO. 95-850-267-XXX		REV A	
EAR# 10443			ANGLES = $\pm 1^\circ$			ENGINEER D.GEORGE		SHEET NO. 2 OF 2		SCALE: 1.0:1.0		PART NO. 95-850-267-XXX	