

PERFORMANCE

Range 0 - 2000 ppm
Sensitivity 18 - 38 nA/ppm CO
Zero in air at 20 °C <10 ppm CO
Resolution 10 ppm CO
Linearity linear across range
Response time, t90 <35 s
Long-term output drift <2% signal/month
Warranty 2 years

OPERATING CONDITIONS

Temperature range -20 to +50 °C
Operating humidity 15 - 90% RH (non-condensing)
Pressure range 90 - 110 kPa (nominal)
Operating circuit see Electrochemical Toxic Sensor Application Note
Applied potential 0 V
Storage life 6 months in original packaging (0 - 25 °C)

PHYSICAL CHARACTERISTICS

Label colour silver
Weight 5 g approx.
Dimensions see outline

This device is designed to be RoHS compliant.

CROSS-SENSITIVITY DATA




GAS	Concentration (ppm)	Sensor Response (As ppm CO)
Hydrogen Sulfide	15	0
Sulfur Dioxide	5	0
Chlorine	10	0
Nitric Oxide	35	-10 to 0
Nitrogen Dioxide	5	0
Hydrogen	100	<50
Ethene	100	<30
Ethanol	200	0

Important Note

Do not solder to the connector pins as this may damage the sensor and thereby invalidate the warranty.

Details on recommended connector pins can be found in the Frequently Asked Questions within the Gas Sensor section of the SGX website.


OUTLINE



All dimensions in mm.
All tolerances ± 0.15 mm unless otherwise stated.

TEMPERATURE DEPENDENCE

EC-4-2000-CO Graph of Zero vs Temperature



EC-4-2000-CO Graph of Net Sensivity vs Temperature

