


- NOTES:
1. MATERIALS AND FINISHES:
BODY = ZINC DIE CAST (ZAMAK #3 PER ASTM-B86),NICKEL PL. (150 MIN/200MAX).THICK OVER
COPPER PL. (100 MIN/200MAX)THICK
CONTACT = BRASS (ALLOY C22530, HARD, CuZn35PbI), GOLD PL. 30 MIN. THICK OVER
NICKEL PL. 100 MIN. THICK OVER NICKEL STRIKE
INSULATOR = PTFE PER ASTM D1710
FAKRA HOUSING = NYLON 46, 30% GLASS FILLED, PER DSM, STANYL, GRADE TE250F6
COLOR PER AMPHENOL SPEC. 349-50688 (REFER TO TABLE BELOW FOR KEY CODE)
FERRULE = SEAMLESS COPPER TUBING, ALLOY 122 (DHP), ASTM-B75 HARD. DRAWN TO ROCKWELL
58-77 ON 30T SCALE, NICKEL PL. 100 MIN.THICK OVER COPPER STRIKE

2. ELECTRICAL:
A. IMPEDANCE: 50 OHM
B. FREQUENCY RANGE: DC - 4 GHz
C. VSWR: 1.180 (DC - 2.0 GHz); 1.225 (2.0 - 4.0 GHz).

3. MECHANICAL:
A. DURABILITY: 100 CYCLES MIN.
B. TEMPERATURE RANGE: -65° C TO 165° C


4. PACKAGING:
A. QUANTITY: TRAY PACK
B. MARKING: TRAYS TO BE MARKED
"AMPHENOL, 2FA2-NXSP-C04-9, AND DATE CODE"

5. RECOMMENDED CABLE ASSEMBLY INSTRUCTIONS
FOUND ON AMPHENOL SPEC. 349-50695



KEY CODE	ASSEMBLY PART #	COLOR	RAL NO.
A	2FA2-NASP-C04-9	JET BLACK	9005
B	2FA2-NBSP-C04-9	CREAM	9001
C	2FA2-NCSP-C04-9	SIGNAL BLUE	5005
D	2FA2-NDSP-C04-9	CLARET VIOLET	4004
E	2FA2-NESP-C04-9	LEAF GREEN	6002
F	2FA2-NFSP-C04-9	NUT BROWN	8011
G	2FA2-NGSP-C04-9	BLUE GREY	7031
H	2FA2-NHSP-C04-9	HEATHER VIOLET	4003
I	2FA2-NISP-C04-9	BEIGE	1001
K	2FA2-NKSP-C04-9	CURRY	1027
L	2FA2-NLSP-C04-9	CARMINE RED	3002
M	2FA2-NMSP-C04-9	PASTEL ORANGE	2003
N	2FA2-NNSP-C04-9	PASTEL GREEN	6019
Z	2FA2-NZSP-C04-9	WATER BLUE	5021

CONFIGURATION CONTROL:
NO CHANGES PERMITTED TO DRAWING WITHOUT
PPAP QUALIFIED CUSTOMER APPROVAL



CUSTOMER OUTLINE DRAWING
ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES ±.015 (0,381 mm) ±.005 (0,127 mm) ± 1°	MATERIAL	DRAWN B.C.GLEISSNER	DATE 19-Jan-08	TITLE FAKRA DUAL STRAIGHT PLUG, C04 CABLE GROUP (RG-58)		Amphenol RF Danbury, CT, USA Tainan, Taiwan Shenzhen, China www.amphenolrf.com		
	REFERENCE EAR# 533.1 & 969.1 GEN# ASSYM4_FAKRA 615X-1834-200 KDC = KEY DESIGN CHARACTERISTICS	ENGINEER MIKE HOYACK	DATE 19-Jan-08					
			APPROVED O. BARTHELMES			DATE 19-Jan-08		
	NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.		CAD FILE I:\FAKRA\2FA2-NXSP-C04-9	CODE ID 74868	DWG SIZE B	DRAWING NO. 2FA2-NXSP-C04-9	REV C	