

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 11_SMA-50-3-73/-99_N

Rev.: B



Description

Straight cable plug

Interface Standards

IEC 60169-15_MIL-STD-348A/310_CECC 22110



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 18 GHz

Mechanical Data

Centre contact plugged
Outer contact crimped
Weight 0.0021 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact
Outer contact
Body
Insulator
Coupling nut
Gasket

Material

Stainless Steel
Stainless Steel
Stainless Steel
PFA / PTFE

Surface Plating

Passivated (Plating)
Passivated (Plating)
Passivated (Plating)

Related Documents

Outline drawing DOU-00007976
Catalogue drawing DOU-00007819
Assembly instruction DOC-0000180072

Ordering Information

Single package 11_SMA-50-3-73/-99_NE
Bulk 100 pcs package 11_SMA-50-3-73/-99_NH

Additional Information

Suitable cable EZ_141_TP_M17

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com