





Low temperature airframe wires (200°C)
ASNE026ICF-U Series

Draka Fileca part number	Conductors		Gauje AWG	Ø O.D.		Nominal weight (g/m)	Rating (Amp)	Conductor resistance maxi 20°C (Ω/km)
	Stranding (n x mm)	Section (mm²)		mini (mm)	maxi (mm)			
F E 0261CF26-U	19 x 0,10	0,15	26	0,75	0,84	1,85	3	160
F E 0261CF24-U	19 x 0,12	0,21	24	0,85	0,94	2,52	4	114
F E 0261CF22-U	19 x 0,15	0,34	22	0,98	1,09	3,74	6,5	60
F E 0261CF20-U	19 x 0,20	0,6	20	1,22	1,34	6,32	11	33,2
F E 0261CF18-U	19 x 0,25	0,93	18	1,45	1,59	9,50	16	21,1
F E 0261CF16-U	19 x 0,30	1,34	16	1,7	1,84	13,41	22	14,5
F E 0261CF14-U	37 x 0,25	1,82	45	1,93	2,10	17,88	30	10,9
F E 0261CF12-U	37 x 0,32	2,98	12	2,41	2,60	28,75	40	6,8
F E 0261CF10-U	61 x 0,32	4,91	10	3,03	3,25	47,20	54	4,1

REMARK

- Breaking strength

● Stretching strength
- AWG 26

> 4,6 daN

> 6 %
- AWG 24

> 6,7 daN

> 6 %

CORES COLORS

- All gauges are white
- ExCept gauge 22 is light green



Route nationale 1 - 60730 SAINTE-GENEVIEVE - Tel: +33 (0)3 44 08 21 21 - Fax: +33 (0)3 44 08 98 86
Web site: www.draka.fr

Ref.: A 67 - © - 2000 - Médiasquare
Passing and / or copying of the document, use or communicate of its content is not permitted without prior authorization. Information subject to change without notice.