

REV.		DATE	DESCRIPTION	
NC		07/16/01	INITIAL RELEASE	

RECOMMENDED
CABLE STRIPPING DIM'S

1/4-36UNS-2A

CRIMP NOTES:
1. CRIMPED FERRULE
HEX CRIMP SIZE .429"
2. CRIMPED CONTACT PIN
HEX CRIMP SIZE .118"

DESCRIPTION	MATERIAL	FINISH	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS DIMENSIONS IN [] ARE IN INCHES FOR CUSTOMER REFERENCE ONLY		APPROVALS		DATE	TITLE			
1 BODY	BRASS	GOLD	DRAWN		G.R.S.		07/16/01	SMA CRIMP JACK (FOR BELDEN 9913, 9914, LMR-400)			
2 INSULATOR	TEFLON	NATURAL	CHECKED								
3 CONTACT PIN	BRASS	GOLD	ISSUED								
4 FERRULE	COPPER	GOLD									
5								UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5-6 = ± 0.2 6-30 = ± 0.4 30-120 = ± 0.8 120-315 = ± 1 315-1000 = ± 1.6 1000-2000 = ± 2.4			
6								SIZE FSQM NO. DWG. NO.			
7								A 99001 132332.DWG			
8								DO NOT SCALE DRAWING			

SCALE	NA	PART NO.	132332	SHEET	1 OF 1
-------	----	----------	--------	-------	--------