

## Coaxial Panel Connector 23\_N-50-0-30/133\_N

### Description

Straight panel receptacle jack, flange mount

Interface standards

IEC 61169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

|                          |        |
|--------------------------|--------|
| Impedance                | 50 Ω   |
| Interface frequency max. | 11 GHz |

#### Mechanical Data

|                   |           |
|-------------------|-----------|
| Number of matings | 500       |
| Weight            | 0.0146 kg |

#### Environmental Data

|                                                      |                  |
|------------------------------------------------------|------------------|
| Operating temperature                                | -65 °C to 125 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant        |

#### Material Data

| Piece Parts    | Material               | Surface Plating       |
|----------------|------------------------|-----------------------|
| Centre contact | Copper Beryllium Alloy | SUCOPRO Plating       |
| Outer contact  | Brass                  | SUCOPLATE (R) Plating |
| Body           | Brass                  | SUCOPLATE (R) Plating |
| Insulator      | PFA / PTFE             |                       |

### Related Documents

|                   |              |
|-------------------|--------------|
| Catalogue drawing | DCA-00010110 |
| Mounting hole     | DOU-00008784 |

### Ordering Information

|                |                     |
|----------------|---------------------|
| Single package | 23_N-50-0-30/133_NE |
|----------------|---------------------|